

'Hi-Flow' Diesel Tank

90lpm 230v bowser pump with 6m 'wrap & hang' hose and auto nozzle fitted in the lockable pump bay.

fuel chief



THE COMPLETE PACKAGE **basic plus**

Fast Fuel, plain and simple

The Basic Plus package is a 90lpm pump kit equipped with a 10um filter, mechanical meter, 6 metres x hose and an auto shut off nozzle. The pump kit (pictured at left) is fitted into the lockable pump bay ensuring the system is safe and secure when not in use.

- Positive displacement, self-priming, rotary electric vane pump.
- 230V, 750 watt, 1400 rpm.
- 120 lpm max flow rate. 90lpm sustainable.
- Suitable for continuous service with thermal overload protection.
- 1" flanged connectors, external filter.

DC Self-bunded Tank Specification

A brand-new design, from the ground up, this tank features an improved inner tank wall with no internal bracing.

The tank that fits in a car space



Fully compliant with AS1940, AS1692

- Capacities range from 2,500L, 5,000L, 10,000L, 15,000L, 20,000L & 45,000L models with large secure cabinet to house all pumps and equipment.
- Full height access door with 3-way locking system and anti-levering design for extra security.
- Cabinet has access hatch through roof to allow safe servicing of tank vent.
- Lockable access door to fuel management terminal and switching.
- Spill sump in cabinet base to contain spillage.
- Sloped floor in inner tank for better water catchment and recovery.
- Water inspection & suction port housed under lockable hatch.
- Large access manhole for maintenance and inspection of inner tank.
- Extra feed and return ports for running auxilliary equipment.
- Lockable fill point with integrated dipstick.
- Offset fill pipe for rapid refuelling with Camlock or dry-break coupling (DC25 nozzle fill only).
- Base of tank sealed in an anti-rust underseal.

Everything securely fitted
in the lockable pump bay



Ask about our hose reel or hose tower delivery options.

Model	SFL	Specifications	Weight Dry	Approvals
DC25	2,375L	1140mmW x 2500mmL x 1500mmH	950kg	AS1940, AS1692
DC50	4,755L	1140mmW x 2950mmL x 2550mmH	1600kg	AS1940, AS1692, AS1657
DC100	9,900L	2300mmW x 2950mmL x 2550mmH	2490kg	AS1940, AS1692, AS1657
DC150	14,800L	2320mmW x 3900mmL x 2520mmH	3626kg	AS1940, AS1692, AS1657
DC200	18,800L	2260mmW x 5850mmL x 2520mmH	4630kg	AS1940, AS1692, AS1657
DC370	37,000L	2260mmW x 10550mmL x 2520mmH	7500kg	AS1940, AS1692, AS1657

fuel chief

AUSTRALIA: 1300 899 038 | www.fuelchief.com.au | E: sales@fuelchief.com.au
NEW ZEALAND: (03) 384 2380 | www.fuelchief.co.nz | E: sales@fuelchief.co.nz