

# Manage Your Fuel Efficiently

Provides fuel management for up to 250 users with fast, precise dispensing at 90 LPM through a 3m hose mast and 7m delivery hose and auto nozzle.



## THE COMPLETE TANK AND FUEL MANAGEMENT PACKAGE business

### Keep an eye on your fuel use

The Business package is a pump kit combined with a P.I.N manual USB download fuel management, complete with proximity tags. The data is then accessed via a web site allowing multiple users to access data.

The pump kit is equipped with a 10um filter, pulse meter, 3-metre high mast affixed to the side of the tank with 7 metres x hose and an auto shut-off nozzle.

### MCS Connect Secure Website Access

Connect from any web enabled PC, tablet or smartphone eliminating the requirement for software. Unlimited access to the MCS Connect website for transaction reconciliation.

- USB Download & Connect to Website. (No Software needed)
- 250 users with key fob function
- 2000 transaction memory
- Total tracking of vehicle/driver fuel usage.
- 230v pump kit @ 90LPM flow rate



### The tank that sits in a car space



### DC Self-bunded Tank Specification

- Capacities range from 2,500L, 5,000L, 10,000L, 15,000L, 20,000L & 45,000L models with large secure cabinet to house all pumps and equipment.
- Full height access door with 3-way locking system and anti-levering design for extra security.
- Cabinet has access hatch through roof to allow safe servicing of tank vent.
- Lockable access door to fuel management terminal and switching.
- Spill sump in cabinet base to contain spillage.
- Sloped floor in inner tank for better water catchment and recovery.
- Water inspection & suction port housed under lockable hatch.
- Large access manhole for maintenance and inspection of inner tank.
- Extra feed and return ports for running auxilliary equipment.
- Lockable fill point with integrated dipstick.
- Offset fill pipe for rapid refuelling with Camlock or dry-break coupling (DC25 nozzle fill only).
- Base of tank sealed in an anti-rust underseal.

Everything securely fitted in the lockable pump bay



Ask about our hose reel or hose tower delivery options.

Model	SFL	Specifications	Weight Dry	Approvals
DC25	2,375L	1140mmW x 2500mmL x 1500mmH	950kg	AS1940, AS1692
DC50	4,755L	1140mmW x 2950mmL x 2550mmH	1600kg	AS1940, AS1692, AS1657
DC100	9,900L	2300mmW x 2950mmL x 2550mmH	2490kg	AS1940, AS1692, AS1657
DC150	14,800L	2320mmW x 3900mmL x 2520mmH	3626kg	AS1940, AS1692, AS1657
DC200	18,800L	2260mmW x 5850mmL x 2520mmH	4630kg	AS1940, AS1692, AS1657
DC370	37,000L	2260mmW x 10550mmL x 2520mmH	7500kg	AS1940, AS1692, AS1657



AUSTRALIA: 1300 899 038 | www.fuelchief.com.au | E: sales@fuelchief.com.au  
NEW ZEALAND: (03) 384 2380 | www.fuelchief.co.nz | E: sales@fuelchief.co.nz