

Manage Your Fuel Easily

Provides entry level fuel management for up to 50 users with fast, precise dispensing at 70 LPM.

fuelchief



THE COMPLETE PACKAGE

economy



Keep an eye on your fuel use

This package provides entry-level fuel management and is ideal for users looking to monitor their fuel usage with simple reporting and quick install.

Using PIN operation to enter user details, this set-up has an on-board memory that will store up to 255 transactions. The manager key is then used to download the data to the PC the specific software is loaded onto, so reports can be generated.

- Complies with AS1940, AS1692 & AS1657.
- Excellent footprint when space is premium.
- Lockable pump bay. Excellent security.
- Rated as minor storage by AS1940.
- Hassle-free.



DC Self-bunded Tank Specification

A brand-new design, from the ground up, this tank features an improved inner tank wall with no internal bracing.

DC Self-bunded Tank Specification

- Capacities range from 2,500L, 5,000L, 10,000L, 15,000L, 20,000L & 45,000L models with large secure cabinet to house all pumps and equipment.
- Full height access door with 3-way locking system and anti-levering design for extra security.
- Cabinet has access hatch through roof to allow safe servicing of tank vent.
- Lockable access door to fuel management terminal and switching.
- Spill sump in cabinet base to contain spillage.
- Sloped floor in inner tank for better water catchment and recovery.
- Water inspection & suction port housed under lockable hatch.
- Large access manhole for maintenance and inspection of inner tank.
- Extra feed and return ports for running auxilliary equipment.
- Lockable fill point with integrated dipstick.
- Offset fill pipe for rapid refuelling with Camlock or dry-break coupling (DC25 nozzle fill only).
- Base of tank sealed in an anti-rust underseal.



Everything securely fitted in the lockable pump bay



Ask about our hose reel or hose tower delivery options.

Model	SFL	Specifications	Weight Dry	Approvals
DC25	2,375L	1140mmW x 2500mmL x 1500mmH	950kg	AS1940, AS1692
DC50	4,755L	1140mmW x 2950mmL x 2550mmH	1600kg	AS1940, AS1692, AS1657
DC100	9,900L	2300mmW x 2950mmL x 2550mmH	2490kg	AS1940, AS1692, AS1657
DC150	14,800L	2320mmW x 3900mmL x 2520mmH	3626kg	AS1940, AS1692, AS1657
DC200	18,800L	2260mmW x 5850mmL x 2520mmH	4630kg	AS1940, AS1692, AS1657
DC370	37,000L	2260mmW x 10550mmL x 2520mmH	7500kg	AS1940, AS1692, AS1657

fuelchief

AUSTRALIA: 1300 899 038 | www.fuelchief.com.au | E: sales@fuelchief.com.au
 NEW ZEALAND: (03) 384 2380 | www.fuelchief.co.nz | E: sales@fuelchief.co.nz