

Manage Your Fuel Efficiently

The Tank and Fuel management set-up for the company with mid-high fuel usage and where cost-control is critical.

fuelchief



THE COMPLETE TANK AND FUEL MANAGEMENT PACKAGE **industry**

Keep an eye on your fuel use

The **Industry Package** is a pump kit combined with a web-based (cloud) fuel management system. Fuel transactions and tank levels are transmitted in real-time to the Total Site manager (TSM) website for full reporting functionality.

The **Sapphire Online Terminal** has a range of capabilities that include the acceptance of all cards for ID, automated filtering of on-road and off-road transactions for tax rebate purposes and the capability of merging external fuel transactions with home-based transactions on the same report.

The **pump dispensing** system is equipped with a 10um filter, pulse meter, 3-metre high mast affixed to the side of the tank with seven (7) metres x hose and auto shut-off nozzle.

- Web based, connected straight to your desktop
- Track vehicles, users & all fuel use in real-time
- Unlimited users
- Unlimited vehicles



The tank that sits in a car space



DC Self-bunded Tank Specification

- Capacities range from 2,500L, 5,000L, 10,000L, 15,000L, 20,000L & 45,000L models with large secure cabinet to house all pumps and equipment.
- Full height access door with 3-way locking system and anti-levering design for extra security.
- Cabinet has access hatch through roof to allow safe servicing of tank vent.
- Lockable access door to fuel management terminal and switching.
- Spill sump in cabinet base to contain spillage.
- Sloped floor in inner tank for better water catchment and recovery.
- Water inspection & suction port housed under lockable hatch.
- Large access manhole for maintenance and inspection of inner tank.
- Extra feed and return ports for running auxilliary equipment.
- Lockable fill point with integrated dipstick.
- Offset fill pipe for rapid refuelling with Camlock or dry-break coupling (DC25 nozzle fill only).
- Base of tank sealed in an anti-rust underseal.

Everything securely fitted in the lockable pump bay



Ask about our hose reel or hose tower delivery options.

Model	SFL	Specifications	Weight Dry	Approvals
DC25	2,375L	1140mmW x 2500mmL x 1500mmH	950kg	AS1940, AS1692
DC50	4,755L	1140mmW x 2950mmL x 2550mmH	1600kg	AS1940, AS1692, AS1657
DC100	9,900L	2300mmW x 2950mmL x 2550mmH	2490kg	AS1940, AS1692, AS1657
DC150	14,800L	2320mmW x 3900mmL x 2520mmH	3626kg	AS1940, AS1692, AS1657
DC200	18,800L	2260mmW x 5850mmL x 2520mmH	4630kg	AS1940, AS1692, AS1657
DC370	37,000L	2260mmW x 10550mmL x 2520mmH	7500kg	AS1940, AS1692, AS1657

fuelchief

AUSTRALIA: 1300 899 038 | www.fuelchief.com.au | E: sales@fuelchief.com.au
NEW ZEALAND: (03) 384 2380 | www.fuelchief.co.nz | E: sales@fuelchief.co.nz