

Self-Powered Diesel Tank

fuelchief

80lpm hi-flow HONDA pump with auto nozzle fitted in the lockable pump bay



THE COMPLETE PACKAGE **standalone**

Where you have no power source,

The ideal solution to pump fuel and pump it fast, for the remote areas where electrical power is unavailable.

Tank

Self-bunded steel tank (tank in a tank) complying with AS1940 & AS1692 with a lockable pump bay.

Pump & Dispensing

One (1) x 2" petrol powered 4-stroke, 4hp Honda pump with an internal bypass.

Flow rate of up to 80lpm at the nozzle with 10m x hose and an auto shut-off nozzle, mounted on a retractable hose reel.

Mechanical meter, and a water filter.

All fitted in the lockable pump bay

**Fuel savings straight to your yard
Don't waste time at the servo**



DC Self-bunded Tank Specification

A brand-new design, from the ground up, this tank features an improved inner tank wall with no internal bracing.

Fully compliant with AS1940, AS1692

- Capacities range from 2,500L, 5,000L, 10,000L, 15,000L, 20,000L & 45,000L models with large secure cabinet to house all pumps and equipment.
- Full height access door with 3-way locking system and anti-levering design for extra security.
- Cabinet has access hatch through roof to allow safe servicing of tank vent.
- Lockable access door to fuel management terminal and switching.
- Spill sump in cabinet base to contain spillage.
- Sloped floor in inner tank for better water catchment and recovery.
- Water inspection & suction port housed under lockable hatch.
- Large access manhole for maintenance and inspection of inner tank.
- Extra feed and return ports for running auxilliary equipment.
- Lockable fill point with integrated dipstick.
- Offset fill pipe for rapid refuelling with Camlock or dry-break coupling (DC25 nozzle fill only).
- Base of tank sealed in an anti-rust underseal.



**Everything securely fitted
in the lockable pump bay**



Ask about our hose reel or hose tower delivery options.

Model	SFL	Specifications	Weight Dry	Approvals
DC25	2,375L	1140mmW x 2500mmL x 1500mmH	950kg	AS1940, AS1692
DC50	4,755L	1140mmW x 2950mmL x 2550mmH	1600kg	AS1940, AS1692, AS1657
DC100	9,900L	2300mmW x 2950mmL x 2550mmH	2490kg	AS1940, AS1692, AS1657
DC150	14,800L	2320mmW x 3900mmL x 2520mmH	3626kg	AS1940, AS1692, AS1657
DC200	18,800L	2260mmW x 5850mmL x 2520mmH	4630kg	AS1940, AS1692, AS1657
DC370	37,000L	2260mmW x 10550mmL x 2520mmH	7500kg	AS1940, AS1692, AS1657

fuelchief

AUSTRALIA: 1300 899 038 | www.fuelchief.com.au | E: sales@fuelchief.com.au
NEW ZEALAND: (03) 384 2380 | www.fuelchief.co.nz | E: sales@fuelchief.co.nz